

E.MIX Marble Fix

Cement-based fixing mortar for marble



E.MIX Marble Fix is a high quality, premixed, dry-set mortar specially designed for fixing marble onto the floor between 5 to 15 mm thick. It is cement-based, water-resistant, used in interior dry and wet conditions.

PRODUCT BENEFITS



USES

E.MIX Marble Fix is for fixing marble between 5 - 15 mm thick. It is also suitable for installing granite tiles. Suitable substrates are concrete, prepacked screed, or cement/sand screed.

TECHNICAL DATA & PHYSICAL PROPERTIES

Colour	Beige
Binder	White Cement
Filler	Graded Sand
Additives	Improve workability, open time, and adhesion strength
Water Demand	Approx. 18 -20% or 7.2-8.0 litres/40 kg bag
Pot Life	Approx. 1 - 2 hours
Tensile Adhesion Strength (BS EN 1348: 2007)	1.4 N/mm ² (After 28 days air-cured)

Specifications are subject to change without notification. Results shown are typical but reflect laboratory test procedures conducted in laboratory conditions. Actual field performance will depend on installation methods and site conditions.

PROCEDURE & APPLICATION



Substrate Preparation

All surfaces must be clean, sound, and free from any laitance, oil, grease, and any contaminants.



Mixing

Add E.MIX Marble Fix with the required amount of clean water. Mix thoroughly with a mechanical mixer until the mixture is homogeneous. Allow mixture to stand for 3-5 minutes for the additives to dissolve. Mix again, and the mortar is ready for use.



Application

For optimal results in tiling, apply the mortar by pressing it firmly against the substrate with a trowel and back buttering the backside of tiles. Notched trowel with higher ridges can be used for applying E.MIX Marble Fix. Press tiles onto the sub-base firmly and knock into position. Adjustment of tiles is possible within 15 minutes after installation. Tiling should not be done under extremely hot, windy, and rainy conditions to avoid adverse effects on adhesion.

The wear resistance and adhesion of E.MIX Marble Fix can be further enhanced by the addition of E.MIX Bond Admix.

SAINT-GOBAIN (SINGAPORE) PTE LTD - 201223252K

2 Venture Drive, #13-18 Vision Exchange, Singapore 608526

(65) 63308288 (65) 63308289 EIS.info@Saint-Gobain.com www.sg.weber

E.MIX Marble Fix

Cement-based fixing mortar for marble

CONSUMPTION

Approx. 1.5 kg/m²/mm thick

PRECAUTION

No further addition of water is allowed to the unused mortar that has exceeded its pot life or has begun to set.

STORAGE & PACKING

E.MIX Marble Fix is available in 40 kg bags.
Shelf life of 12 months if unopened and kept in sheltered and dry conditions.

HEALTH & SAFETY

E.MIX Marble Fix contains cement, which may produce an allergic effect. Material may irritate eyes and skin. In case of contact with eyes, rinse immediately with plenty of water, and seek medical assistance. After contact with skin, wash immediately with plenty of soap and water. Please keep out of reach of children.

*Note: Because it is not possible to give specific instructions for the various site conditions or to control the applications, the information on this Technical Data Sheet is for general guidance only. Saint-Gobain (Singapore) Pte Ltd reserves the rights to amend the contents of the data sheet at its sole discretion. (Nov '22)

*bizSAFE*₃



SAINT-GOBAIN (SINGAPORE) PTE LTD - 201223252K

2 Venture Drive, #13-18 Vision Exchange, Singapore 608526

(65) 63308288 (65) 63308289 EIS.info@Saint-Gobain.com www.sg.weber

SAINT-GOBAIN